

N 50
D79MH52N1
90 CM CHIMNEY HOOD



Optional accessories

Z5102X1	Active carbon filter
Z5102X5	Recirculating kit

The wall-mounted rangehood: a functional design element in the kitchen.

- ✓ Extraction rate: at 730 m³/h, it quickly ensures optimal kitchen air quality.
- ✓ Especially quiet: high performance at just 55 dB.
- ✓ LED lighting: for perfect, energy-efficient illumination of the cooktop.
- ✓ Intensive speed setting with reset: automatically resets the hood to regular speed setting after 6 min.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : Australia Standards, CE, Eurasian, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 582-908/582-1018
 Height of product, without chimney (mm) : 46
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 18.901
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 460
 Boost position output recirculating (m³/h) : 440
 Maximum output recirculating air (m³/h) : 340
 Boost position air extraction (m³/h) : 730
 Number of lights : 3
 Noise level (dB) : 55
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242004183808
 Connection Rating (W) : 139
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : Gardy plug w/ earthing
 Installation typology : Wall-mounted



4 242004 183808

N 50
D79MH52N1
90 CM CHIMNEY HOOD

Features

- 90 cm Chimney hood
- Box slimline design
- For wall mounted installation
- Appliance colour: Stainless steel
- Suitable for ducted extraction and recirculation
- Accessories required for recirculated extraction: Recirculating kit
- EASY Installation
- Electronic controls
- Push button controls (3 power levels + 2 intensive levels) with 7-segment display
- Extraction rate according to EN 61591 \varnothing 15 cm:
max. Normal use 460 m³/h
Intensive 730 m³/h
- Efficient BLDC brushless motor technology
- Automatic intensive revert setting - 6 min
- Automatic run on for Automatic run on - 10 min
- 3 x 3 Watt LED Lights
- Softlight with dimming function
- Dishwasher safe metal grease filters
- Saturation indicator for grease filters
- Noise min./max. Normal Level: 45/55 dB
Noise max. Intensive setting: 65 dB
- Additional noise insulation mats for optimised sound absorption

Technical Information

- Diameter pipe \varnothing 150 mm (\varnothing 120 mm enclosed)
- Power rating: 139 W
- Dimensions exhaust air (HxWxD): 628-954 x 900 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 900 x 500 mm
- Electrical cable length 1.3 m

N 50
 D79MH52N1
 90 CM CHIMNEY HOOD

Dimensioned drawings

