

iQ500
LB78574AU
70 cm Fully integrated rangehood



The powerful canopy rangehood is concealed above the cooktop.

- ✓ The highly efficient 730 m³/h extraction rate provides ideal air quality in the kitchen.
- ✓ The energy saving LED lighting with dimmer function ensures ambient lighting and optimal visibility when cooking.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert to previous setting after 6 min.
- ✓ 63 dB (540 m³/h) - 150mm ducted.

Features

Technical Data

Typology : Traditional
 Approval certificates : Australia Standards, CE, VDE
 Length electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 418mm x 676mm x 264mm
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 650
 Net weight (kg) : 12.354
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 630
 Boost position output recirculating (m³/h) : 310
 Maximum output recirculating air (m³/h) : 300
 Boost position air extraction (m³/h) : 730
 Number of lights : 2
 Noise level (dB) : 66
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable aluminium
 EAN code : 4242003700853
 Connection Rating (W) : 277
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : AU plug
 Installation typology : Built-in

Optional accessories

LZ55750	Recirculating kit
LZ55651	Active carbon filter
LZ46810	CleanAir active carbon filter



4 242003 700853

iQ500
LB78574AU
70 cm Fully integrated rangehood

Features

Design & Innovation

-
-
- Appliance colour: Stainless steel
- Electronic controls with low-lift push buttons
- 2 x 1 Watt LED lights
- metal grease filters with stainless steel cover

Convenience

- low-lift push buttons controls for power and light

Power and Mode of Operation

- Suitable for ducted and re-circulating operation
- Accessories required for recirculation mode: CleanAir Module
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 630 m³/h
 - Intensive 730 m³/h
- 3 power levels plus intensive setting
- Intensive operation automatic revert - 6min
- Rim ventilation
- Twin channel high performance fan motor

Cleaning

- Dishwasher safe metal grease filters
- Cassette with alu frame

Safety and Quality

- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
 - Max. normal use: 66 dB(A) re 1 pW (52 dB(A) re 20 µPa sound pressure)
 - Intensive: 69 dB(A) re 1 pW (55 dB(A) re 20 µPa sound pressure)

Dimensions (HxWxD)

- For installation in a kitchen cabinet
- 120 or 150 mm tube connection diameter
- Appliance dimensions (HxWxD): 418 x 700 x 282 mm
- Built-in dimensions (HxWxD): 418 x 676 x 264 mm
- Electrical cable length 1.5 m
- Power rating: 277 W

iQ500
LB78574AU
70 cm Fully integrated rangehood

Dimensioned drawings

