

iQ700
LF21BA552 stainless steel
120 cm Stainless steel Box slimline
brand design hood

A



The ceiling-mounted island chimney hood is perfect for all kitchen islands.

- ✓ The 720 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking
- ✓ Extremely quiet at a mere 64 dB.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert after 6 min.

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, Ukraine, VDE
 Length electrical supply cord (cm) : 130
 Height of the chimney (mm) : 698-878/747-999
 Height of product, without chimney (mm) : 46
 Net weight (kg) : 39.2
 Type of control : Electronic
 Number of speed settings : 3-stage + 2 intensive
 Maximum output air extraction (m³/h) : 560
 Boost position output recirculating (m³/h) : 510
 Maximum output recirculating air (m³/h) : 440
 Boost position air extraction (m³/h) : 720
 Number of lights : 4
 Noise level (dB) : 64
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable stainless steel
 Odour filter : No
 Operating Mode : Convertible
 Delay Shut off modes : 10M
 Optional accessories : LZ00XXP00, LZ12285, LZ12310, LZ12385, LZ12410, LZ12510, LZ12530, LZ56200, LZ57600
 Type of lamps used : LED
 Total power of the lamps (W) : 12
 Grease filter type : Multilayer
 Connection Rating (W) : 272
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : Gardy plug w/ earthing
 Installation typology : Island
 Material body : Stainless steel
 Approval certificates : CE, Ukraine, VDE
 Plug type : Gardy plug w/ earthing
 Dimensions of the product, with chimney (if exists) (in) : / x x
 Dimensions of the packed product (in) : 34.84 x 24.01 x 52.16
 Net weight (lbs) : 86
 Gross weight (lbs) : 110
 Motor location : Integrated motor in hood chimney
 No-return airflow flap : No
 Length electrical supply cord (cm) : 130
 Dimensions of the product, with chimney (if exists) (mm) : 744-924 x 1200 x 650
 Dimensions of the packed product (HxWxD) (mm) : 885 x 610 x 1325
 Net weight (kg) : 39.2
 Gross weight (kg) : 50.0



iQ700
LF21BA552 stainless steel
120 cm Stainless steel Box slimline
brand design hood

Features

Design

- 120 cm Stainless steel Box slimline brand design Table ventilation hood
- on both sides, Push button

Comfort

Technical Information

- Suitable for ducted and re-circulating operation only
- Total power of motors: 260 W
- Clean Air recirculating kit indicator available
- White electronic display
- Push button with 7-segment display
- 3-stage + 2 intensive
- Main switch: On/Off Control
- Intensive op. revert dur.: 6 min.
- Air quality sensor
- Boost function
- Twin channel high performance fan motor
- 1000EE
- 4 x LED 3W
- Softlight with dimmer function
- Cascade Filter
- Rim extraction
- 4 metal grease filters
- Saturation display filter: grease- and charcoal filter
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 560 m³/h
 - Intensive 720 m³/h
- Automatic intensive revert
- Noise level: 50 dba
- Additional noise reduction insulation

Dimensions:

- Dimensions exhaust air (HxWxD): 744-924 x 120 cm x 65 cm
- Dimensions recirculating with cleanAir module (HxWxD): 812-1044mm x 120 cm x 65 cm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Total Connected load: 272 W
- Connecting cable 130 cm

iQ700
LF21BA552 stainless steel
120 cm Stainless steel Box slimline
brand design hood

Dimensioned drawings

