



RB492701
Two-door bottom freezer with integrated ice maker
with temperature controlled drawer
Fully integrated appliance
Width 36" (91.4 cm)

Width 36" (91.4 cm)
Stainless steel interior
Generous LED lighting concept
Solid aluminum door bins
Net volume 19.8 cu.ft.
Integrated automatic ice maker with fixed water connection
One motorized glass shelf, adjustable when fully loaded
One asymmetrically split glass shelf
Fully extendable freezer drawer with practical divider
ENERGY STAR® qualified

Color Variants

RB492701
with temperature controlled drawer
Fully integrated appliance

Optional accessories

RA450000
Mechanical particle filter
RA450010
Activated charcoal filter for water filter system including saturation indicator

Required installation accessories

RA460000
Installation kit for side-by-side installation (for connecting any two columns)
RA460010
Additional side heating element

Installation Accessories

RA421910
Stainless steel door panel with handles
RA425110
Long stainless steel door handle
RA425910
Short stainless steel door handle
RA460030
Connecting element for vertically split fronts (for fridge-freezer combination with one door)
RA461910
Ventilation grill, stainless steel

Operation

Electronic precision temperature control with digital temperature display.

Technical features

Dynamic cool air distribution with Multi-Flow Air System.
 Automatic defrosting with defrost water evaporation.
 Activated charcoal air filter.
 Energy-saving vacation mode.
 Open-door and malfunction warning system.

Cooling compartment

Net volume 14.3 cu. ft.
 No-frost technology with fast cooling.
 Temperature adjustable from 35 °F to 46 °F (+2 °C to +8 °C).
 2 safety glass shelves, 1 of which is motorized.
 1 asymmetrically split safety glass shelf, manually adjustable.
 2 fully extendable drawers with transparent front.
 Bright interior lighting with LED sidewall pillars.
 2 height adjustable door bins, one large gallon door bin.
 1 door bin with transparent front flap.

Temperature controlled drawer

Net volume 0.9 cu. ft.
 No-frost technology.
 1 continuous, fully extendable temperature controlled drawer close to 32F with transparent front, manually controllable.

Freezer compartment

Net volume 5.8 cu. ft. (166 liters).
 No-frost technology with fast freezing.
 Temperature adjustable from 7 °F to -9 °F (-14 °C to -25 °C).
 2 fully extendable drawers.
 Interior lighting with two spot lights.

Ice dispenser

Integrated automatic ice maker in the freezer compartment, with fixed water connection.
 Ice maker can be switched off independently.
 Ice cube production approx. 3.1 lb (1.4 kg)/24 h.
 Removable ice storage bin with approx. 6.6 lb (3 kg) capacity.

Planning notes

Flat hinge.
 Door hinge right, reversible.
 Door opening angle of 115°, optional 90° door stop.
 Max. door panel weight:
 Door 77 lb.
 Drawer 22 lb.

Product Features

Multi-Flow Air Tower

Yes

SUPERCOOL

Yes

SUPERFREEZE

No

Carbon Air Filter

No

Temperature Controlled Drawer

No

Humidity Control Drawer

Yes

Number of Door Bins - Refrigerator

2

Adjustable Door Bins - Refrigerator

No

Tilt-Out Door Bins - Refrigerator

Yes

Gallon Storage Bins

1

No. cooking modes

3

Door Hinge

Right reversible

Adjustable Shelves - Refrigerator

2

Number of Shelves - Freezer

Yes

Reversible Door Hinge

Yes

Adjustable Shelves - Freezer

No

Consumption and connection features

UPC code

825225899914

Color / Material housing

Colour.Material door

Panel ready

Not possible

Silence level (dBA)

41

Watts (W)

588

Current (A)

10

Volts (V)

120

Frequency (Hz)

60

Total annual energy consumption (kWh)

590.9

Energy Star® qualified

Yes

Approval certificates

ETL, ETL C

Power Cord Length

139 1/3"

Required cutout size (HxWxD) (in)

x 84" x 35 3/4"

Appliance Width (in)

35 3/4"

Height (in)

83 3/4 "

Depth (in)

24"

Capacity in 0.75l (bordeaux bottles)

Total unit gross capacity (cu. ft.) - AHAM

20

Product packaging dimensions

(HxWxD) (in)

88.97 x 39.37 x 29.52

Refrigerator Gross capacity (cu. ft.)

14

Freezer Gross capacity (cu ft)

6

Net weight (lbs)

483

Gross weight (lbs)

526

SKU

RB492701

2018-01-21

Page 1

Shut-off valve for water connection must be planned next to the appliance and always be accessible.

If the water pressure exceeds 116 psi, connect pressure relief valve between water tap and hose set.
 Cold water connection required.
 Electrical location 6" above ground in lower left corner of unit.
 Water pressure 29 to 116 psi.

Consumption data


Energy consumption 1.619 kwh/24 h.
 Noise level 41 dB.

Rating

Total rating 0.588 kW.
 Total Amps: 10 A.
 120 V / 60 Hz
 Connecting cable 139 1/3" with plug.
 Supply hose 118" with 3/4" connection.

RB492701
 Two-door bottom freezer with integrated
 ice maker
 with temperature controlled drawer
 Fully integrated appliance
 Width 36" (91.4 cm)

2018-01-21
 Page 2



The drawing is based on a cabinet panel width of 3/4" (19 mm) and a Gaggenu cabinet handle height of 1 5/16" (49 mm).

